According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 30.11.2007

DOW CORNING FIRE STOP(R) 400 INTUMESCENT SEALANT

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY					
Trade name	:	DOW CORNING FIRE STOP(R) 400	0 INTUMESCENT SEALANT		
Company	:	Dow Corning S.A. rue Jules Bordet - Parc Industriel - Zo B-7180 Seneffe Belgium	ne C		
Service	:	Dow Corning Central Europe	Tel: +49 6112371 Fax: +49 611237609		
		Dow Corning Northern Europe	Tel: +44 1676528000 Fax: +44 1676528001		
		Dow Corning Southern Europe	Tel: +33 472841360 Fax: +33 472841379		
Emergency Phone Number	:	Dow Corning (Barry U.K. 24h) Dow Corning (Wiesbaden 24h) Dow Corning (Seneffe 24h)	Tel: +44 1446732350 Tel: +49 61122158 Tel: +32 64 888240		
E-mail address (Safety Data Sheet)	:	sdseu@dowcorning.com			
Use of the substance/preparation	:	Flame retardants and fire preventing			

2. HAZARDS IDENTIFICATION

The principal hazards of the product as supplied are:

May cause sensitization by skin contact.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Acrylic dispersion

Hazardous Ingredients:

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification	
5-Chloro-2-methyl-3(2H)-isot hiazolone, mixt. with 2-methyl-3(2H)-isothiazolone	55965-84-9	Exempt or not available	<=0.01	T C	R23/24/25 R34 R43
				Ν	R50/53

4. FIRST AID MEASURES		
On contact with eyes	:	No first aid should be needed.
On skin contact	:	Flush with water. Wipe off. Obtain medical attention.

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 30.11.2007

DOW CORNING FIRE STOP(R) 400 INTUMESCENT SEALANT

If inhaled	:	Remove to fresh air.
On ingestion	:	No first aid should be needed.

5. FIRE FIGHTING MEASURE	ES	
Suitable extinguishing media	:	On large fires use dry chemical, foam or water spray (fog). On small fires use carbon dioxide (CO2), dry chemical or water spray. Water can be used to cool fire exposed containers.
Unsuitable extinguishing media	:	None known.
Hazards during fire fighting	:	None known.
Special protective equipment/procedures	:	A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Hazardous Combustion Products	:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds.

6. ACCIDENTAL RELEASE MEASURES					
Personal precautions	:	Wear proper protective equipment.			
Precautions to protect the environment	:	Do not allow large quantities to enter drains or surface waters.			
Methods for cleaning up	:	Scrape up and place in a container fitted with a lid. The spilled product produces an extremely slippery surface.			

7. HANDLING AND STORA	7. HANDLING AND STORAGE				
Advice on safe handling	:	General ventilation is recommended. Avoid skin and eye contact.			
Advice on storage	:	Do not store with oxidizing agents.			
Specific uses	:	Refer to technical data sheet available on request.			
Unsuitable packaging materials	:	None known.			

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 30.11.2007

DOW CORNING FIRE STOP(R) 400 INTUMESCENT SEALANT

Engineering Controls	:	Ventilation : Refer to Section 7
Exposure controls for hazard	lous	components
Name	(CAS-No. Exposure Limits
None of the components have a	assig	ned exposure limits.
Personal protection equipment	<u>nt</u>	
Respiratory protection	:	Respiratory protection is not normally required.
Hand protection	:	Chemical protective gloves or gauntlets should be worn and removed correctly to avoid skin contamination: Silver shield(TM). 4H(TM). Regarding glove's breakthrough time,contact your chemical protective glove supplier.
Eye protection	:	Safety glasses should be worn.
Skin protection	:	Wear impervious overalls in circumstances where significant skin contact can occur.
Hygiene measures	:	Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking. Remove contaminated clothing immediately.
Environmental exposure controls	:	Refer to section 6 and 12.
Additional information	:	None known.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form:	Paste		Colour:	See product name	Odour:	Very little
Important	t health, safety an	d envi	ronmental inf	<u>formation</u>		
Explosive	properties	:	No			
Specific G	Fravity	:	1.5			
Oxidizing	properties	:	No			
The above in	formation is not intende	ed for use	e in preparing pro-	duct specifications. Contact	Dow Corning be	fore writing specifications.
10. STABIL	ITY AND REAC	FIVIT	Y			

IV. STADILITT AND REACTIVITT					
Stability	Stable under normal usage conditions.				
Conditions to avoid	None established.				

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 30.11.2007

DOW CORNING FIRE STOP(R) 400 INTUMESCENT SEALANT

Materials to avoid	:	Can react with strong oxidising agents.
Hazardous decomposition products	:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely
		burned carbon compounds.

11. TOXICOLOGICAL INF	11. TOXICOLOGICAL INFORMATION		
On contact with eyes	:	May cause temporary discomfort.	
On skin contact	:	Repeated contact can cause sensitisation and allergic dermatitis.	
If inhaled	:	No adverse effects are normally expected.	
On ingestion	:	No adverse effects are normally expected.	
Other Health Hazard Information	:	This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the current physical form of the product, which is not in a respirable form.	

¹ Based on product test data.

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION

Environmental fate and distribution

Solid material, insoluble in water. No adverse effects are predicted.

Ecotoxicity effects

No adverse effects on aquatic organisms are predicted.

Bioaccumulation : No bioaccumulation potential.

Fate and effects in waste water treatment plants

No adverse effects on bacteria are predicted.

13. DISPOSAL CONSIDE	RATION	S
Product disposal	:	Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Packaging disposal	:	Dispose of in accordance with local regulations. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 30.11.2007

DOW CORNING FIRE STOP(R) 400 INTUMESCENT SEALANT

14. TRANSPORT INFORMATION

Road / Rail (ADR/RID)

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION

Labelling according to EEC Directive			
Contains	: 5-Chloro-2-methyl-3(2H)-isothiazolone, mixt. with 2-methyl-3(2H)-isothiazolone		
Symbols	: Xi Irritant.		
R-phrases	: R43 May cause sensitization by skin contact.		
S-phrases	: S24 Avoid contact with skin. S37 Wear suitable gloves.		
National legislation / regulations			
Ozone depleting chemicals	: No ozone depleting chemicals are present or used in manufacture.		
<u>Status</u>			
EINECS	: All ingredients listed, exempt or notified (ELINCS).		
1			

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 30.11.2007

DOW CORNING FIRE STOP(R) 400 INTUMESCENT SEALANT

16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed., **R34** Causes burns., **R43** May cause sensitization by skin contact., **R50/53** Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.