

Maxogen product specifications

JC60 filters – available in cylindrical or cone shape



JC60






JC60C



JC60FC

JC60, JC60C and JC60FC – Dimensions and BHP ratings



Part number	A I/D neck	B O/D neck	C Diameter	D Neck	E Length	F	G	H	J	BHP* Rating
JC60/58	58	61	149	33	153	121	114	152	114	200
JC60/60	60	63	149	52	172	121	114	152	114	220
JC60/63	63	66	149	52	172	121	114	152	114	240
JC60/67	67	70	149	54	194	121	114	152	114	270
JC60/70	70	73	149	54	194	121	114	152	114	290
JC60/73	73	76	149	50	190	121	114	152	114	300
JC60/78	78	81	149	44	186	121	114	152	114	310
JC60/80	80	83	180	55	215	152	149	–	–	450
JC60/86	86	89	180	53	213	152	149	–	–	480
JC60/93	93	96	180	50	210	152	149	–	–	500
JC60/99	99	102	180	50	210	152	149	–	–	520
JC60/114	114	117	180	45	200	152	149	–	–	530
JC60/124	124	127	180	40	200	152	149	–	–	540
JC60/149	149	152	203	44	265	225	149	–	–	600

All dimensions are in mm.

* BHP ratings are for cylindrical-shaped filters and are a guide only. Cone-shaped filters are rated approximately 10% less

Non-standard overall lengths are available on standard fitting necks. BHP ratings may then be different.

JC60FC filters are used in our carbon RAB65 airboxes. They can also be used as remote air filters

Important: All Maxogen filters must be oiled prior to use. See accessories leaflet for filter oils